

# Fiberoptic Lenses and Mounting Brackets



**FMB-1**  
 (8.4 mm diam.)  
 Standard Fiberoptic  
 Mounting Bracket  
 Use with Threaded Glass  
 Fiberoptic



**FMB-2** (5.1 mm diam.)  
**FMB-3** (3.1 mm diam.)  
 Miniature Glass or Plastic  
 Fiberoptic Mounting  
 Brackets



**FPA-1**  
 Slip-on Polarizing Adaptor  
 Lens (2 Required)  
 Slips over end of  
 Model F-A-36 Straight  
 Light Guides only



**FPA-2**  
 Friction Mount Polarizing  
 Adaptor Lens (2 Required)  
 Friction mounts onto  
 F-A-36P Straight Light  
 Guides only



**GLA-1**  
 1/4" X 1"  
 Slip-on Lens Assembly  
 Slips on Model  
 EH-4001 plastic fibers



**GLA-2**  
 Long Range Lens  
 for Through-Beam  
 Use with M4 Tips



**HLA-1**  
 3/8" X 1" Threaded  
 Slip-on Lens Assembly  
 Slips on Model EH-4001  
 plastic fibers



**HLA-2**  
 Spot Focus Lens for  
 Diffused Beam  
 Use with M6 Tips  
 Focal Point .50" (12.7 mm)



**UAC-12**  
 Slip-on Long Range Plastic  
 Lens, Use on .187" O.D.  
 straight or right angle  
 fiber tip or .040" fiber



**UAC-15**  
 Threaded Long Range Glass  
 Lens, 2" Focal Point  
 Fits any standard threaded  
 tip Glass Fiberoptic  
 Lg. 1 3/8" (35 mm)



**UAC-5**  
 Threaded Spot Focus Plastic  
 Lens, 1" Focal Point  
 Fits any standard threaded  
 tip Glass Fiberoptic  
 Lg. 2" (51 mm)



**UAC-5G**  
 Threaded Spot Focus Glass  
 Lens, 1" Focal Point  
 Fits any standard threaded  
 tip Fiberoptic  
 Lg. 2" (51 mm)



**NFA-50**  
 .5" Nylon Fiberoptic Adaptor,  
 50 pieces, Insert adapts F1 and F4  
 optical blocks to all .040" diam.  
 cut-to-length plastic fiberoptic  
 light guides.



**NFA12-50**  
 .25" Nylon Fiberoptic  
 Adaptor, 50 pieces,  
 Use to adapt UAC-12  
 Lens to .040" diam.  
 plastic fibers.



**PFC-1**  
 Plastic Fiber Cutter