



### Main features

- Powerful embedded PLC
- Scalable
- Wide availability of communication ports
- Real-time solution
- Unique programming software

### Main applications

- Plastics
  - Packing
  - Wood
  - Metalworking

### PROFILE

The GF\_VEDO line of operator terminals is a compact and affordable machine control solution.

A single product integrates a PLC and graphic pages display [SCADA], making the creation of automation solutions extremely rapid and economical.


Panel sizes range from 6.5" to 15" with touch screen or integrated keyboard and horizontal or vertical installation.

The panel uses a GEODE 32 bit processor with RAM from a minimum of 256MB to a maximum of 512MB, based on the operating system installed.

Extremely important characteristics are the complete absence of moving parts and a fan-free cooling system.

All of the products are programmable with GF\_PROJECT programming environment.

Products based on Windows XPe are available for use of third-party applications as an alternative to products with a real-time operating system.




## TECHNICAL DATA

GF_VEDO ML	65CT	65CK	104CT	104CK	121CT	150CT
						
Function	Display control [PLC+HMI]					
Touch	resistive	-	resistive	-	resistive	resistive
Keyboard key/led	NO -	YES 47/1	NO -	YES 54/1	NO -	NO -
Resolution	VGA 640x480		SVGA 800x600		SVGA 800x600	XVGA 1024x768
Backlighting	CCFL		LED		CCFL	CCFL
Processor	32bit Geode LX900, 600 MHz					
Memory	256-512MB DRAM					
Flash memory	1 x CF 1 GB/2GB					
I/O Pheripherals						
ethernet	2 x 10/100Mbps					
CAN	1 x CANopen					
Serials	1xRS232,1xRS485					
USB	4xUSB2.0 Host					
PS2	2x mouse/keyboard					
TF serial	1x machine keyboard					
Models horizontal vertical	YES -	YES -	YES YES	YES -	YES YES	YES YES
Protection	IP65 front, IP20 rear					
Temperature operating storage	0...+50°C -20°C...+70°C					
Humidity	5...95% HR non condensing					
Power supply	24 VDC ±25%					

## Dimensions


See size table for the different models



## Table dimensions

Model		frame		dima						dima		
		A	B	C	D	E	F	G	H	I	L	
6.5" touch	65CT	187.0	133.0	75.5	68.0	177.5	125.0	166.0	114.5	179.5	127.0	mm
10.4" touch	104CT	266.0	192.5	68.5	61.0	256.0	182.5	166.0	114.5	258.0	184.0	mm
12,1" touch	121CT	305.0	231.0	76.0	68.0	292.0	218.0	166.0	114.5	295.0	222.0	mm
15" touch	150CT	369.0	273.0	76.0	68.0	356.0	260.0	166.0	114.5	359.0	262.0	mm
6.5" with keypad	65CK	187.0	230.0	76.0	68.0	177.5	220.0	166.0	114.5	180.0	222.0	mm
10.4" with keypad	104CK	266.0	289.0	76.0	68.0	256.0	279.0	166.0	114.5	258.0	281.0	mm

## CONNECTIONS



No	Name	Description
1	FIELDBUS	[Optional] -CAN layer 2
2	RS232	Serial RS-232
3	MOUSE	PS/2 Mouse (green)
4	PC-KEY	PS/2 keyboard (violet)
5	ETH1	Ethernet 10/100 Base-T
6	USB	USB 2.0 Host (500 mA)
7	ETH2	Ethernet 10/100 Base-T
8	USB	USB 2.0 Host (500 mA)
9	KEY & LED	Fieldbuses keyboard
10	RS485	RS-485 optically-isolated serial
11	AUTO-START	Auto-on
12	24 V d.c.	Power supply
13	AUX	Slot reserved for future uses
14	CF	Compact Flash
15	BATTERY	Battery jumper
16	ROTARY	Rotary configuration selector
17	PC-KEY	Auxiliary PS/2 keyboard

## ORDERING CODE

GF\_VEDO ML

--	--	--	--	--

MODEL	
6.5" with keyboard	65CK
6.5" touch	65CT
10.4" with keyboard	104CK
10.4" touch	104CT
12.1" touch	121CT
15" touch	150CT

OPERATING SYSTEM	
VxWorks CF: 1GB RAM: 256MB	VW1
VxWorks CF: 1GB RAM: 512MB	VW2
WinXP Embedded CF: 1GB RAM: 256MB	XE0
WinXP Embedded CF: 2GB RAM: 512MB	XE1

EXPANSION 1	
None	00
CANopen + RS232 + Autostart	C1

EXPANSION 2	
None	00
RS232 + Autostart	S1 (*)

LEXAN	
Gefran	G
Neutral	N

(\*) only in absence of the expansion1 (C1)

Please, contact GE FRAN sales people for the codes availability.

## ACCESSORIES

<b>Keyboards</b>	Fieldbuses keyboard to manage movements	<b>TF</b>
<b>Supply</b>	Stabilized supply 100....240Vac/24Vdc, 5A	<b>GF_PS5</b>
<b>Software</b>	Integrated programming environment	<b>GF_Project</b>

GEFRAN spa reserves the right to make any kind of design or functional modification at any moment without prior notice



In conformity to ECC 2004/108/CE (EMC) and 2006/95/CE (LVD) with reference to: **EN 61131-2** (product) **EN 61010-1** (safety).

# GEFRAN

**GEFRAN spa**  
 via Sebina, 74  
 25050 Provaglio d'Iseo (BS)  
 Tel. +39 030 9888.1 - fax +39 030 9839063  
 Internet: <http://www.gefran.com>

DTS\_GFVEDO ML\_01-2013\_ENG